



OUTDOOR FIXED BET

The Outdoor Fixed Housing Building Entrance Terminal provides a outdoor option for Demarcation utilizing Tool-Less IDC termination and a variety of input options. The protector field of this BET accommodates industry standard 5-pin protectors. Available in 25, 50 and 100 fixed pair units and factory installed & tested solid state and gas tube protectors.

INDUSTRY STANDARDS

IDC Connector - Telcordia TR-NWT-001195
 BET - Telcordia GR-937/GR-2916
 NID - Telcordia GR-49/GR-239
 UL Listed

ORDERING INFORMATION

OF	XXX	X	F	XXX	X	XX
PAIR COUNT	OUTPUT	HOUSING	PROTECTION	INPUT	OEM	
025	N = None	F = Fixed	NOP = No Protectors	G = Stub 25'	Contact Sales	
050	M = Toolless IDC & NID		3B1ES = 300V Solid State Black, no Test Points	H = 4005 GPM (MS2 Gel)		
100	P = Toolless IDC		3B1FS = 240V Solid State Black, no Test Points	K = 4005 DBM (MS2 Dry)		
300*	R = Toolless IDC & RJ21		3B3ES = 300V Solid State Red, no Test Points	P = 710 SC1 (710 Gel)		
	S = RJ21		3B3FS = 240V Solid State Red, no Test Points	T = 710 SD1 (710 Dry)		
	T = Toolless IDC & Cross Connect		3C1ES = 300V Solid State Black, Test Points	N = Raw Cable		
			3C1FS = 240V Solid State Black, Test Points			
			3C3ES = 300V Solid State Red, Test Points			
			3C3FS = 240V Solid State Red, Test Points			
			6B1E = 350V Gas Tube, Black, PTC, no Test Points			
			6C1E = 350V Gas Tube, Black, PTC, no Test Points			
			3B1E = 350V Gas Tube, Black, no Test Points			
			3C1E = 350V Gas Tube, Black, Test Points			

*300 pair unit is comprised of a kit containing three 100 pair units with associated parts required for stacking